

PCIe8g3 KU-40G

PCIe Gen3 x8 board: Kintex Ultrascale FPGA, 40G QSFP+, and 10G SFP/+s

Photo not available

Description

The PCIe8g3 KU-40G is a fast, versatile PCI Express (PCIe, Gen3) x8 interface with one 40G QSFP+ and up to two 10G SFP/+ ports. It supports 1/10/40GbE, OC3/12/48/192 (STM1/4/16/64), or OTU1/2/2e/2f.

Each port links to the user-interface (UI) FPGA for serialization / deserialization (SERDES) and clock recovery. Each port has its own reference clock, programmable for 10–210 MHz.

The UI FPGA is a Xilinx Kintex Ultrascale (U035, 060, 085, or 115) with access to two independent 64-bit wide blocks (2 GB each, 4 GB total) of DDR3 DRAM which can act as data buffers. This UI FPGA configures from flash at power-on, and can be reconfigured as many times as desired without powercycling. Up to five images are available, depending on which UI FPGA model is used.

The PCIe FPGA provides up to 16 independent DMA channels via EDT FPGA configuration files.

An optional Lemo supports time code input (1 pps or IRIG-B), with user-configurable output and two cabling options.

EDT provides FPGA configuration files to support 1GbE and 10GbE at the PHY layer; OC3/12/48/192 and OTU1/2/2e/2f (raw, framed, framed and descrambled); and demultiplexing. Custom files can be requested.

Applications

Telecommunications monitoring, recording, and processing

SONET/SDH to ethernet conversion

Multiple other network processing applications

Features

PCIe (Gen3) x8 interface with one 40G QSFP+ and up to two 10G SFP/+s

Data formats: 1/10/40GbE, OC3/12/48/192 (STM1/4/16/64), OTU1/2/2e/2f

FPGA (UI): One user-configurable Xilinx Kintex Ultrascale (035, 060, 085, 115)

FPGA (PCIe): One (up to 16 DMA channels via EDT FPGA configuration files)

DRAM (DDR3): Two independent 64-bit blocks of 2 GB each (4 GB total)

EDT intellectual property for 10GbE PCS and PMA layers, SONET/SDH framing, demultiplexing, and G.709 framing

Optional Lemo for time code input, with user-configurable output

Specifications

Product Type	PCIeGen3 x8 board: Kintex Ultrascale FPGA; 1 40G QSFP+ and 1-2 10G SFP/+s for up to 40GbE / OC192 (STM64) / OTU2f.			
FPGA Resources + DMA	UI FPGA (user-configurable) PCIe FPGA	1 Kintex Ultrascale (U035, U060, U085, or U115) 1 Altera Arria V GZ for up to 16 independent DMA channels		
Memory	DDR3 DRAM, two independent blocks of 2 GB (4 GB total); each block is 64 bits wide - for snapshot recording / data buffering			
Clocks (Reference)	Up to four (one per port), each independently programmable from 10 to 210 MHz with limited support for reference loop timing.			
Data Rates	Dependent on such factors as data format, main board, and system variables.			
Data Format (I/O)	Via multiple ports, the board supports various data formats as shown below: 1/10/40GbE, OC3/12/48/192 (STM1/4/16/64), OTU1/2/2e/2f). Also provided is a time code input (to connect to an external source) for 1 pps, IRIG-B, or other input, with user-configurable output.			
Transceivers	The board has multiple transceiver options, as shown below.			
	Up to two SFP/+*	ELECTRICAL (1GbE)	OPTICAL (10GbE) SFP/+*	SFP/+*
			1550 nm	1310 nm
			850 nm	
Output power (dBm)	-	-	-2 to +3 / 0 to +4	-9.5 to -3 / -8.2 to +0.5
Center wavelength (nm)	-	-	1500-1580 / 1530-1565	1270-1360 / 1260-1355
Sensitivity (dBm)	-	-	-28 / -23	-18 / -10.3
Max. input power (dBm)	-	-	-9 / -7	0 / +0.5
Connector	RJ45 transceiver		LC	LC
	* An SFP at 1550, 1310, or 850 nm can support 1GbE, OC3/12/48 (STM1/4/16), or OTU1. An SFP+ at 1550 or 1310 nm can support 10GbE, OC192 (STM64), or OTU2/2e/2f - or, at 850 nm, 10GbE only.			
	Up to one QSFP+, 40GbE	850 nm		
Output power (dBm)			-7.6 to -1.0	
Center wavelength (nm)			840-860	
Sensitivity (dBm)			-5.4	
Max. input power (dBm)			+3.4	
Connector			1x12 MPO	
Cooling	Active heat sink			
Connectors	One optional 7-pin Lemo for time code input (1 pps or IRIG-B) with user-configurable output One RJ45 or LC on each SFP/+ as shown above One MPO on QSFP+			
Cabling	For optional time code input, from source to Lemo For other cabling, consult EDT for purchase options.	One DB9 (for 1 pps or IRIG-B) or BNC (for IRIG-B only)		
Physical	Weight Dimensions	8.5 oz. (with active heat sink, but without transceivers) 6.6 x 4.2 x 0.75		
Environmental	Temperature (operating / non-operating) Humidity (operating / non-operating)	0° to 40° C / -40° to 70° C 1% to 90%, non-condensing at 40° C / 95%, non-condensing at 45° C		
System and Software	System must have a PCI Express bus (8 or 16 lanes) that is not dedicated to display use only. Software is included for Windows and Linux; for versions, see www.edt.com .			

Ordering Options

- FPGA: U035 / U060 / U085 / U115
- Transceivers: [options above]
- Optional time code input:
 - 1 Lemo connector + cabling (DB9 or BNC)

Bold is default. For more options, see main board detail. **Ask** about custom options.